




AMI
ADVANCED MICRO INSTRUMENTS

MODEL 3000RS PORTABLE TRACE H₂S

DEPENDABLE H₂S MEASUREMENTS MADE EASY FOR THE FIELD

The **MODEL 3000RS** Portable H₂S Analyzer is the perfect choice for safely and accurately measuring ppm levels of H₂S in the natural gas industry. Exclusive innovations and distinctive features are designed into a compact and rugged package. Our patented Cell Block and high-performance sensor produce a safe, fast and reliable H₂S measurement in harsh applications. All AMI portables are outfitted with a datalogging feature that serves as a useful tool when spot-checking multiple sites per day.

ELIMINATOR CELL BLOCK™ ADVANTAGE

Compact and Leak Free Design - This unique sample system approach virtually eliminates all potential leak paths while optimizing flow efficiencies. The sample system and sensor pocket are machined directly into a solid metallic block and interconnected with precision-drilled, intersecting gas passages - eliminating the need to use long lengths of tubing and leak-prone compression fittings. The uniquely engineered metering valve and flow meter are integrated directly into this compact block.

COMMON APPLICATIONS

- ▶ NATURAL GAS
- ▶ BIOGAS
- ▶ WASTEWATER

ACCURATE & COST-EFFECTIVE MEASUREMENTS

Stain tubes can detect the presence of H₂S, but differences in technique and the subjective reading method can lead to unacceptable errors as high as ± 20%. The ongoing cost of single-use tubes add up over months of regular sampling. The one-time investment in a **MODEL 3000RS** provides an accurate and unambiguous tool for quickly measuring ppm levels of H₂S and verifying compliance with stringent tariff limits.

TRULY PORTABLE AND DESIGNED FOR THE FIELD

At just 5 lbs. (7.3 kg), the **MODEL 3000RS** is the smallest, lightest, and most accurate portable Trace H₂S Analyzer in the industry.

SPOT-CHECKING OR UNATTENDED MONITORING

The **MODEL 3000RS** is a great choice for quick and easy spot-checking of inlet/outlet gas at H₂S treatment facilities. When extended monitoring is required, operators can utilize the onboard data logger to record a time-stamped record of H₂S levels and temperature at a user programmable interval. The long-life rechargeable battery makes unattended operation possible when trying to track down small, intermittent leaks.

MODEL 3000RS

PHYSICAL & ELECTRICAL SPECIFICATIONS

WEIGHT	GAS CONNECTIONS	WETTED PARTS
5.0 lbs (2.3 kg)	Input: Female Quick Disconnect fitting. Supplied with mating male quick disconnect fitting coupled to ¼" compression fitting Exhaust: Male barb fitting for ¼" flexible tubing	316 S.S. fittings, electro-less nickel plated cell block, gold-plated contacts, acrylic flow meter & O-rings (Viton, kalrez, and Buna-N)
POWER		
Rechargeable Nickel Cadmium Batteries (350 hours of continuous operation)		



Note: 2-year Warranty for Parts & Labor for any defects in materials or workmanship. 1-year Warranty for H₂S sensors

OPERATIONAL SPECIFICATIONS

OUTPUT RANGES (USER SELECTABLE)		AMBIENT OPERATIONAL TEMPERATURE	FLOW RATE (RECOMMENDED)	INLET GAS PRESSURE
STANDARD RANGES	OPTIONAL HIGH RANGE SENSOR			
0 – 10 ppm 0 – 50 ppm 0 – 100 ppm 0 – 200 ppm	0 – 100 ppm 0 – 500 ppm 0 – 1000 ppm 0 – 2000 ppm	25°F to 115°F (–3.9°C to 46°C)	0.1 to 2.0 SCFH (0.05 – 1.0 Lpm)	0.5 – 150 psig (0.03 – 10.3 bar)

SENSOR & ANALYZER PERFORMANCE SPECIFICATIONS

LOW RANGE SENSOR	HIGH RANGE SENSOR	90% FULL SCALE RESPONSE TIMES @ 1.5 SCFH (0.75 Lpm) FOR SPECIFIC RANGES		REPEATABILITY	ACCURACY	APPROVALS
Max Range 0 – 200 ppm	Max Range 0 – 2000 ppm	<120 sec for 0 – 100 ppm	<120 sec for 0 – 2000 ppm	±1% of range or ±0.2 ppm of H ₂ S, whichever is greater	±1.5% of full range range at constant conditions	CSA-approved for Class 1, Div. 1, Groups B,C,D hazardous areas

RESPONSE TO OTHER GASES IN THE SAMPLE GAS (GIVEN THAT 100 PPM OF THE LISTED GAS IS PRESENT)

Methyl Mercaptan (40 ppm) Carbon monoxide (4 ppm) Hydrogen (1 ppm) Sulfur dioxide (18 ppm) *Note: For complete list, contact AMI*

ANALYZER KEY FEATURES

ELIMINATOR CELL BLOCK™	Contains a Complete Sample System with all components fully integrated, including the flow meter, metering valve and 4-way Selection (ON/OFF) Valve
ANALOG OUTPUT	0.0 – 1.0 VDC
COMMAND CENTER	Software that works across AMI's Analyzers and gives users access to advanced functions: <ul style="list-style-type: none"> ▶ Calibration Details ▶ Security Settings ▶ Time-stamped data logger with adjustable interval recording for: <ul style="list-style-type: none"> - H₂S measurement - Temperature - Battery voltage
ACCESSORIES	<ul style="list-style-type: none"> ▶ Carrying Case ▶ Auxiliary Power Adapter ▶ Flexible High Pressure Sample Tubing



Representantes / Distribuidores Exclusivos

Argentina

Tel: (+54 11) 5352 2500
Email: info@dastecsr.com.ar
Web: www.dastecsr.com.ar

Uruguay www.dastecsr.com.uy

Paraguay www.dastecsr.com.py

Bolivia www.tecdas.com.bo

225 Paularino Avenue
Costa Mesa, CA 92626

714.848.5533

www.amio2.com

