

# EXP Controller

## Intelligent Control - Oil in Water Probe

Customer inspired innovation



**Leveraging decades of innovation experience for the Oil & Gas industry, Inov8 Systems introduce the next generation of products for an evolving market with dynamic demands.**

### Features

- New rapid wave ultrasonic self cleaning
- Choice of standard or high-resolution spectrometry feature
- Low power DC voltage requirements - other options including AC available
- Multiple Communication options for Management Capabilities
- Probe with integrated control - zero footprint
- Adjustable flange mount for probe insertion depth
- Integral, configurable colour display
- Less than 25KG weight
- 316SS Exd Hazardous ATEX, IECEx and C1D1 Certification

### Benefits

- Low cost of ownership with no regular maintenance, no routine calibration and no added chemicals
- Simple to use interface for set-up and control
- Lightweight with easy access to instrument without removing from process.
- Meets hand carry requirements for choppers
- Minimal installation requirements (24VDC, Exd)
- Remote Monitoring and Automatic Process Control
- Continuous real-time measurements; <1 sec response to process changes
- 24 month standard warranty

# Technical Specifications



Representantes / Distribuidores Exclusivos

Argentina

Tel: (+54 11) 5352 2500

Email: [info@dastecsrl.com.ar](mailto:info@dastecsrl.com.ar)

Web: [www.dastecsrl.com.ar](http://www.dastecsrl.com.ar)

Uruguay [www.dastecsrl.com.uy](http://www.dastecsrl.com.uy)

Paraguay [www.dastecsrl.com.py](http://www.dastecsrl.com.py)

## OPERATING CONDITIONS:

Ambient Temperature	-20C to 60C
Process Temperature	-20C to 200C
Design Pressure	100barg (higher options available)
Standard Operating Pressure	0 - 10barg (higher options available)
Flow Velocity	0.5 - 10 m/s

## MECHANICAL:

Dimensions	Probe length 0.75m to 5.0m
Weight	<25KG
Process Connections	2" ANSI Flange (others sizes available)
Wetted Parts	316L SS Standard (others available)
Non-Wetted Parts	316L SS
Enclosure / Probe	IP66 / IP68

## MEASUREMENT:

Light Source	Solid State CW 3mW Laser or Deep UV LED
Measurement Method	Fluorescence Spectrometry
Range	PPB - 10,000 ppm*
Range (Deep UV)	ppb - 50,000ppm*
Accuracy	+/- 1%
Sample Rate	< 1 sec
Repeatability	< +/- 1%

## CONTROLLER INTERFACE:

Analogue	1 x 4-20mA, HART (optional)
Ethernet	10/100 Mbps
Wifi	
Digital	2 x Volt free contacts

\* Under controlled conditions and dependent on API of oil

## ELECTRICAL:

Power Voltage / Current	24VDC / 6A (options available for 24VDC 1A and 230/110VAC)
Power Consumption	20W nominal, 140W peak
Cable Entries	3 entries - M20x1.5mm

## COMPLIANCE:

### Directives:

- 2014/68/EU Pressure Equipment Directive, module A1
- 2014/34/EU ATEX Directive Exd IIG Class 1 Division 1, Zone 1

### Standards:

FM3600	Electric Equipment for use in Hazardous Locations General requirements
FM3615	Explosion Proof Electrical Equipment General Requirements
FM3810	Electrical Equipment For Measurement, Control and Laboratory Use
ANSI/IEC 60529	Degrees of Protection Provided By Enclosures (IP code)
CSA-C22.2 No. 30	Explosion Proof Enclosures For Use In Class 1 Hazardous Locations.
CSA-C22.2 No. 142	Process Control Equipment
CSA-C22.2 No. 60529	Degrees of Protection Provided By Enclosures
IECEX EN 60079-0	Explosive atmospheres Part 0: Equipment General Requirements
IECEX EN 60079-1	Explosive atmospheres Part 1: Equipment protected by flameproof enclosures "d"
IMO107(49)	Marine 15 ppm regulations
DNVGL-CP-0485	Clean Design 5 ppm regulations