

THE BEST SOLUTION FOR ACCURATE RESULTS IN ALL APPLICATIONS

HQD™ meters and high performance pH electrodes



Easy to handle, providing accurate results



HQD benchtop multi-meter

Probes for every application


For high volume labs or applications where performance is critical, Intellical™ Red Rod pH electrodes incorporate proven technology to deliver superior accuracy and response times, even when measuring challenging samples over a wide temperature range.

Standard lab probes and rugged field probes are available to measure a wide variety of parameters. Several probes use speciality designs for specific measurement applications.

All Intellical probes are automatically recognized by HQD meters and retain calibration history and method settings to minimize errors and setup time.

Red Rod technology

The unique Red Rod Technology provides not only fast response time but also long-term accuracy and reproducibility. Red Rod electrodes feature:




Fast and accurate response thanks to the symmetrical electrode chain formed by the internal and external Red Rod reference elements.

Stable signal as the Red Rod Technology protects the reference elements from light interference. Saturated KCl salt-bridge aids stable liquid junction potential.

Wide temperature range (0–100 °C) thanks to fast temperature response of Red Rod Technology.

The symmetry of Red Rod electrodes means that the iso pH is the same as the zero pH which provides **highly reproducible results** even when temperature fluctuations occur.

Trouble-free liquid junction as Red Rod encapsulation of reference elements means no silver ions and therefore less risk of clogging.



Full specifications of the electrodes featured in the table are available on our website or you can call your local office.

Select the best pH electrode for your application

	PHC101	PHC108	PHC201	PHC281	PHC301	PHC705A	PHC705	PHC725	PHC729	PHC735	PHC745	PHC805
Red Rod technology						•	•	•	•	•	•	
Type of sample												
High solids content										B	A	
Alkaline solutions				B	A							
Non aqueous media											A	
TRIS Buffer				B						A		
High viscosity										B	A	
Ultra-pure water										A	B	
Semi-solid samples (cheese, meat...)		A										
Application/industry												
Water/environment												
Low ionic strength				B								A
Wastewater	A		B									
Pool / Spa			A	B								
Sea water				A						B		
Drinking water				A			B					
Boiler/Cooler				A						B		
Chemical												
Galvanic baths												A
Photography baths												A
Paint												A
Lacquer												A
Agriculture												
Soils (in water)										A		
Soils with high level of salt										A		
Irrigation water			A									B
Suspensions							A					B
Biology/pharmacy												
Agar		B			A							
Blood									B		A	
Ultra-pure water										A	B	

	PHC101	PHC108	PHC201	PHC281	PHC301	PHC705A	PHC705	PHC725	PHC729	PHC735	PHC745	PHC805
Red Rod technology						•	•	•	•	•	•	
Cosmetics												
Fat, cream, cosmetics		B										A
Emulsions										B	A	
Skin									A			
Food/beverage												
Soft drinks								A		B		
Cacao and derivatives												A
Wine, must, vinegar										A		B
Juices, canned vegetables										A	B	
Hops, beer					B			A				
Liqueur								A		B		
Oil, creams, mayonnaise		B										A
Jam		B								A		
Milk								A		B		
Yoghurt, curdled milk		B								A		
Brine			B								A	
Cheese, meat, fruit		A										
Bread dough		A										
Paper/textiles												
Paper									A			
Paper pulp or paste		B									A	
Textiles (fabrics and prints)									A			
Textiles (dyes and colorings)											A	
Leather									A			
Fur (treatment bath)				B							A	

A=Recommended Choice B=Alternative

All probes read from 0–14 pH other than PHC101 (2–14), PHC108 (2–12) and PHC729 (0–12).

Temperature range: 0–50 °C for PHC101 | 0–60 °C for PHC108 | 0–80 °C for PHC201, PHC281, PHC301, PHC805 | 0–100 °C for PHC705A, PHC729 | -10–100 °C for PHC705, PHC725, PHC735, PHC745

HQD meters



Easy to use in the field

The wide variety of rugged probe options available for the portable meter means it is perfect for field use. All connections between the meter and the probe are secure and waterproof. Connectors can be color-coded for quick identification. Information is clearly displayed on one screen with back light for low light conditions. Display results can be enlarged for easier reading.

Simple and fast lab setup

Offering a complete portfolio of water testing parameters and a simple benchtop setup, this meter provides the ultimate in lab analysis. The intuitive user interface with guided calibration ensures accurate results, and with a large, backlit LCD screen, the meter is simple to read even if measuring 2 parameters simultaneously.

Parameter	Portable meters				Benchtop meters		
	HQ11D	HQ14D	HQ30D	HQ40D	HQ411D	HQ430D	HQ440D
pH	•		•	•	•	•	•
Conductivity, TDS, salinity, resistivity		•	•	•		•	•
Dissolved Oxygen (LDO)			•	•		•	•
ISE			•	•		•	•
ORP/Redox potential	•		•	•	•	•	•
Inputs for Intellical probes	1	1	1	2	1	1	2
Casing IP Rating	IP67				IP54		
Dimensions (HxWxD), weight	36 mm x 95 mm x 197 mm 323 g (without batteries)				86 mm x 175 mm x 234 mm 850 g		

Detailed technical specifications, electrodes for additional parameters, buffer solutions and accessories are available. Please visit our website or give us a call.



Distribuidor autorizado de HACH en:

 Argentina

Tel: (+54 11) 5352 2500

Email: info@dastecsrl.com.ar

Web: www.dastecsrl.com.ar

 Uruguay www.dastecsrl.com.uy

 Paraguay www.dastecsrl.com.py



Be Right™